

4120 series 1/4 DIN controllers take advantage of the latest SMD technology. Software has been refined and offers logical menu structures and advance noise immunity. By using the unique "SEL" function, the user has the flexibility of assigning the parameters to be shown at the operator level. The 4120 offers a wide variety of options to meet your control needs.

Manual control of the output is standard with offset and shift functions to allow process values to be corrected for intrinsic offsets and in-site calibrations. Dual alarms can be independently configured as process alarm, deviation alarm, deviation band alarm or latching alarm.

- Fuzzy Logic
- Ramp rate function
- Security Config
- UL/CSA/CE
- Timer Function
- Nema 12
- 3 scans/second



FDC-4120 1/4 DIN CONTROLLER

FDC-4120 SPECIFICATIONS

POWER

90-264VAC, 50/60Hz
20-32VAC/VDC

INPUT

Thermocouple (T/C): Type J,K,T,E,B,R,S,N
RTD: PT 100 ohm RTD (DIN 4370 or JIS)
Linear: -10 to 60mV
Range: User configurable
Accuracy: Typically better than $\pm .25\%$ of span
Cold Junction Compensation: 0.1°C/°C ambient typical
Sensor Break: Protection mode configurable
External Resistance: 100 ohms maximum
Normal Mode Rejection: 60 dB
Common Mode Rejection: 120 dB
Sample Rate: 3 times per second

CONTROL

Proportional Band: 0-200°C (0-360°F)
Reset (Auto): 0-3600 seconds
Rate (Derivative): 0-1000 seconds
Ramp Rate: 0-200.0°C (0-360.0°F)/minute
Dwell: 0-3600 minutes
Cycle Time: 0-120 seconds

On-Off: with adjustable hysteresis (0-20% of span)

Control Action: Direct and reverse

INDICATION

Process Display: 0.56" red LED, 4 digits
Setpoint Display: 0.4" green LED, 4 digits
Status Indicator: Out1, ALM1, ALM2, °C and °F.

CONSUMPTION

Less than 5VA

ENVIRONMENTAL AND PHYSICAL

Operating Temperature: -10 to 50°C
Humidity: 0-90% non-condensing
Insulation: 20M ohms minimum (500VDC)
Breakdown: AC 2000V, 50/60Hz, 1 minute
Vibration: 10-55Hz, amplitude 1mm
Shock: 200m/s² (20G)
Weight: 8.46 oz. (240 grams)
Dimensions: 3.77" (H) x 3.77" (W) x 2.08" (D)

ORDERING INFORMATION

Enter a number in each box which corresponds to the specifications you want when ordering the FDC-4120.

FDC-4120

--	--	--	--	--	--	--	--

POWER INPUT

- 4: 90-264VAC
- 5: 20-32VAC/VDC
- 9: Special Order

SIGNAL INPUT

- 5: Configurable
- 9: Special Order

RANGE CODE

- 1: Configurable
- 9: Other

CONTROL MODE

- 3: PID/On-Off Control

OUTPUT 1 OPTION

- 0: None
- 1: Relay 3A/240VAC resistive
- 2: SSR Drive rated 20mA/24V
- 3: 4-20mA linear, maximum load 500 ohms
- 4: 0-20mA linear, maximum load 500 ohms
- 5: 0-10VDC linear, minimum impedance 500K ohms
- 9: Other

OUTPUT 2 OPTION

- 0: None

ALARM OPTION

- 0: None
- 2: Dual Relays 2A/240VAC resistive
- 9: Other

COMMUNICATIONS

- 0: None

