




TSREH Enclosure / Control Panel Heaters

Product Highlights

- ✓ Prevents condensation or freezing of electronics located within enclosures and control panels
- ✓ Easy-to-install mounting plate
- ✓ Air sensing thermostat for most models
- ✓   



Specifications:

- Heater vulcanized to an aluminum plate for easy installation
- Aluminum mounting plate has two mounting slots that are 1/4" (6mm) by 5/32" (4mm) centered in a 1/2" (12mm) flange for mounting
- Suggested mounting method is at the bottom of the enclosure, mounted vertically
- 120VAC. Other voltages available upon request
- 48" (1219mm) PFA extruded leads
- Safe to operate. No exposed electrical connections
- Overall thickness (blanket and bracket): 0.140" (3.6mm) nominal; Bracket is 0.090" (2.3mm) thick aluminum
- Exposure temperature range: -70°F to 392°F (-57°C to 200°C)
- Moisture, chemical, and radiation resistant

Ordering Information:

Width* in (mm)	Length in (mm)	Mounting Center in (mm)	Total Watts	Thermostat		Part Number 120VAC
				Opens	Closes	
2.5 (64)	6 (152)	4 (102)	60	without	thermostat	TSREH600
2.5 (64)	6 (152)	4 (102)	60	60°F (15°C)	40°F (4°C)	TSREH640
2.5 (64)	6 (152)	4 (102)	60	140°F (60°C)	110°F (43°C)	TSREH6110
2.5 (64)	6 (152)	4 (102)	60	180°F (82°C)	150°F (65°C)	TSREH6150
2.5 (64)	12 (305)	9 (229)	120	without	thermostat	TSREH1200
2.5 (64)	12 (305)	9 (229)	120	60°F (15°C)	40°F (4°C)	TSREH1240
2.5 (64)	12 (305)	9 (229)	120	140°F (60°C)	110°F (43°C)	TSREH12110
2.5 (64)	12 (305)	9 (229)	120	180°F (82°C)	150°F (65°C)	TSREH12150

* Dimensions listed are for heater and bracket; actual heater width is 1/2" (13mm) less

Other sizes and thermostat settings are available upon request